SATCO NUVO

Project Name

Location Prepared By



NUVO 65-575R1

2X2 LED EM BACKLIT FLAT PANEL

Notes

rw] 08-14-2025 23:3

Height (in.)
Width (in.)

Length (in.)

General		
Status	Active	
Fixture Type	Backlit Flat Panel	
Finish	White	
Wattage	20W/30W/40W	
Lumen Output	2200L-4600L	
CCT (Kelvin)	3500K/4000K/5000K	
IP Rating	IP20	
Indoor or Outdoor Fixture	Indoor	
Panel Size	2x2	
Smart Product Info		
IOT Enabled	No	
Integrated Camera	No	

Technology	LED
Color Temperature	Warm to Cool White
CRI	80+
Voltage	120V-277V
Beam Angle	120
Rated Hours	50000
Operating Temperature	-17C (+1.4F) to +45C (+113F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming Only
Photocell or Sensor	No Photocell
Lens Material	Poly methyl methacrylate (PMMA)
Surge Protection	Built-in surge protection - 2KV
Weight (lb.)	7.94
Material	Aluminum / Steel

3.06

23.75

23.75

Compliance	
Safety Listing	cETLus - Listed
Location Rating	Damp
UL Application	LED Panel Luminaire
ENERGY STAR	No
DLC Approved	Yes
DLC ID	S-J0MT7W; S-JP9ZK5
NSF Approved	Yes
Air Tight Rated	No
IC Rated	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class A
Flicker Free	Yes
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	Driver Specs - VDC38-48V; 430/620/810mA
Warranty	5-Years

