

Project Name

Location

Prepared By



NUVO 65-586R1

2X4 LED EM BACKLIT FLAT PANEL

Notes

(www) 08-13-2023 00:25:57

General

Status	Active
Fixture Type	Backlit Flat Panel
Finish	White
Wattage	30W/40W/50W
Lumen Output	3300L-5750L
CCT (Kelvin)	3500K/4000K/5000K
IP Rating	IP20
Indoor or Outdoor Fixture	Indoor
Panel Size	2x4

Smart Product Info

IOT Enabled	No
Integrated Camera	No

Specifications

Technology	LED
Color Temperature	Warm to Cool White
CRI	80+
Voltage	120V-347V
Beam Angle	120
Rated Hours	50000
Operating Temperature	-17C (+1.4F) to +45C (+113F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming Only
Photocell or Sensor	No Photocell
Lens Material	Poly methyl methacrylate (PMMA)
Surge Protection	Built-in surge protection - 2KV
Weight (lb.)	11.46
Material	Aluminum / Steel

Dimensions

Height (in.)	2.88
Width (in.)	23.75
Length (in.)	47.72

Compliance

Safety Listing	cETLus - Listed
Location Rating	Damp
UL Application	LED Panel Luminaire
ENERGY STAR	No
DLC Approved	Yes
DLC ID	S-AM02LE; S-BDG3F6
NSF Approved	Yes
Air Tight Rated	No
IC Rated	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class A
Flicker Free	Yes
SDS Sheet	LED_Fixture

Additional Information

Additional Information	Driver Specs - VDC38-48V; 630/810/1030mA
Warranty	5-Years