SATCO NUVO

Project Name

Location



Prepared By

NUVO 65-624

25W LED CANOPY LIGHT

Notes

www] 01-15-2024 02:40:0

Status		
Substitute 65-624R1 Fixture Type Canopy Finish Bronze Wattage 25W Lumen Output 2800L-3322L CCT (Kelvin) 3000K/4000K/5000K IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED Color Temperature Warm to Cool White CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature -30C (-22F) to +50C (+122F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listed Location Rating Wet	General	
Fixture Type Canopy Finish Bronze Wattage 25W Lumen Output 2800L-3322L CCT (Kelvin) 3000K/4000K/5000K IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED Color Temperature Warm to Cool White CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature -30C (-22F) to +50C (+122F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant	Status	Active
Finish	Substitute	65-624R1
Wattage 25W Lumen Output 2800L-3322L CCT (Kelvin) 3000K/4000K/5000K IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED Color Temperature Warm to Cool White CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature -30C (-22F) to +50C (+122F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing cULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC ID PLNTBHU	Fixture Type	Canopy
Lumen Output 2800L-3322L CCT (Kelvin) 3000K/4000K/5000K IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED Color Temperature Warm to Cool White CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature -30C (-22F) to +50C (+122F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing Safety Listing CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC ID		
CCT (Kelvin) 3000K/4000K/5000K IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED Color Temperature Warm to Cool White CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature -30C (-22F) to +50C (+122F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Incomplance Safety Listing CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGY0NY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale	Wattage	25W
IP Rating	Lumen Output	2800L-3322L
IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED Color Temperature Warm to Cool White CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature -30C (-22F) to +50C (+122F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes FCC Compliant	CCT (Kelvin)	3000K/4000K/5000K
Specifications	IP Rating	IP65
Technology Color Temperature Warm to Cool White CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature -30C (-22F) to +50C (+122F) Dimmable Ves-Dimmable Dimming Note Dimming Note Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale California Status Lawful for sale Lawful for sale California Prop 65 Lead ROHS Compliant Yes FCC Compliant Yes FCC Compliant Yes	Indoor or Outdoor Fixture	Outdoor
Color Temperature CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature Dimmable Polycarbonate (PC) Surge Protection Weight (lb.) Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) Compliance Safety Listing Location Rating UL Application DLC Approved DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated CA T20 / T24 Rationale California Status Lawful for sale California Prop 65 Lead ROULO ADDOOR COMPLIANT Results (PC) Warm to Cool White 80+ 80+ 80+ 80+ 80+ 80+ 80+ 80	Specifications	
Color Temperature CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature Dimmable Polycarbonate (PC) Surge Protection Weight (lb.) Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) Compliance Safety Listing Location Rating UL Application DLC Approved DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated CA T20 / T24 Rationale California Status Lawful for sale California Prop 65 Lead ROULO ADDOOR COMPLIANT Results (PC) Warm to Cool White 80+ 80+ 80+ 80+ 80+ 80+ 80+ 80	Technology	LED
CRI 80+ Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature -30C (-22F) to +50C (+122F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGY0NY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes FCC Compliant		
Voltage 100V-277V Beam Angle 150 Rated Hours 50000 Operating Temperature -30C (-22F) to +50C (+122F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGY0NY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 ROHS Compliant Yes FCC Compliant Yes	·	
Beam Angle Rated Hours Operating Temperature Journable Dimmable Dimming Note Lens Material Polycarbonate (PC) Surge Protection Weight (lb.) Dimensions Height (in.) Compliance Safety Listing Location Rating UL Application DLC Approved DLC ID PLNTBHUGYONY B.U.G. Rating IC Rated CA T20 / T24 Rationale California Status California Prop 65 Rols Raterial Source Protection - 2.5KV Weight (lb.) 4.41 Aluminum Alloy Dimensions CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale California Status Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead ROHS Compliant Yes FCC Compliant Yes		
Rated Hours Operating Temperature Dimmable Dimming Note Lens Material Polycarbonate (PC) Surge Protection Weight (lb.) Dimensions Height (in.) Compliance Safety Listing Location Rating UL Application DLC Approved DLC ID PLNTBHUGYONY B.U.G. Rating IC Rated CA T20 / T24 Rationale California Status California Status California Prop 65 Lead RoHS Compliant Polycarbonate (PC) Built-in surge protection - 2.5KV 4.41 Aluminum Alloy DLC 4.41 Aluminum Alloy Outdoor CULus - Listed CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes CA T20 / T24 Rationale California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant		
Operating Temperature Dimmable Ves-Dimmable Ves-Dimmable Dimming Note O-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) Compliance Safety Listing Location Rating UL Application DLC Approved DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated CA T20 / T24 Rationale California Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes FCC Compliant Yes FCC Compliant Yes PLOV Dimming Only A 10-10V Dimming Only Description Outly Built-in surge protection - 2.5KV 4.41 Aluminum Alloy DLO Built-in surge protection - 2.5KV 4.41 Aluminum Alloy Outloor D.O.3 PLNTBHUGY PLNTBHUGY PLNTBHUGYONY B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes		
Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGY0NY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 RoHS Compliant Yes FCC Compliant Yes		
Dimming Note Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing CULus - Listed Location Rating UL Application DLC Approved DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale California Status Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead RoHS Compliant Yes FCC Compliant Polycarbonate (PC) Built-in surge protection - 2.5KV 4.41 Aluminum Alloy Ut. 41 Aluminum Alloy Outdoor CULus - Listed Vet UL S- Listed Vet TUL S- Listed Vet Touthory Touthory Textures Not Regulated Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead RoHS Compliant Yes		· · · · · · · · · · · · · · · · · · ·
Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2.5KV Weight (lb.) 4.41 Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes		
Surge Protection Weight (lb.) Aluminum Alloy Dimensions Height (in.) Safety Listing Location Rating UL Application DIC Approved DLC ID DLC ID DLC ID DLC Rating IC Rated CA T20 / T24 Rationale California Status California Status California Prop 65 California Prop 65 California Prop 65 Campliant Built-in surge protection - 2.5KV 4.41 Aluminum Alloy Built-in surge protection - 2.5KV 4.41 Aluminum Alloy 4.41 Aluminum Alloy Built-in surge protection - 2.5KV 4.41 Aluminum Alloy Wet UL Application Dutdoor Energy Star No PLNTBHUGY0NY B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale California Status Lawful for sale in California Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant		· · · · · · · · · · · · · · · · · · ·
Weight (lb.) Material Aluminum Alloy Dimensions Height (in.) Width (in.) Compliance Safety Listing Location Rating UL Application DLC Approved DLC ID B.U.G. Rating IC Rated CA T20 / T24 Rationale California Status Title 20 / 24 Status California Prop 65 RoHS Compliant Aluminum Alloy 4.41 Aluminum Alou 4.41 Aluminum Alloy 4.41		· · · · · · · · · · · · · · · · · · ·
Material Aluminum Alloy Dimensions Height (in.) 3.13 Width (in.) 10.03 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGYONY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 RoHS Compliant Yes FCC Compliant		
Height (in.) Height (in.) Width (in.) Compliance Safety Listing Location Rating UL Application Energy Star DLC Approved DLC ID B.U.G. Rating IC Rated CA T20 / T24 Rationale California Status California Status California Prop 65 RoHS Compliant Yes 10.03 CULus - Listed Wet ULus - Listed Vet PLNTBHUGYONY Betting To Dutting To Exempt - Fixtures Not Regulated Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant		· · · · · · · · · · · · · · · · · · ·
Height (in.) Width (in.) 10.03 Compliance Safety Listing Location Rating UL Application Cutdoor Energy Star DLC Approved DLC ID PLNTBHUGY0NY B.U.G. Rating B1-U3-G1 IC Rated CA T20 / T24 Rationale California Status Title 20 / 24 Status California Prop 65 RoHS Compliant FCC Compliant 10.03 CULus - Listed Wet Vet PLNTBHUGY0NY B1-U3-G1 T20 Exempt - Fixtures Not Regulated Lawful for sale in California Title 20 / 24 Status Lead FCC Compliant Yes FCC Compliant		Aldifficial Alloy
Width (in.) Compliance Safety Listing	Dimensions	
Safety Listing cULus - Listed Location Rating Wet UL Application Outdoor Energy Star No DLC Approved Yes DLC ID PLNTBHUGY0NY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant	Height (in.)	3.13
Safety Listing Location Rating Wet UL Application Outdoor Energy Star DLC Approved PLNTBHUGY0NY B.U.G. Rating IC Rated CA T20 / T24 Rationale California Status Title 20 / 24 Status California Prop 65 RoHS Compliant CULus - Listed Wet Wet UL Application Outdoor PLNTBHUGY0NY B1-U3-G1 T20 Exempt - Fixtures Not Regulated Lawful for sale in California Lead RoHS Compliant Yes FCC Compliant	Width (in.)	10.03
Location Rating UL Application Energy Star DLC Approved DLC ID PLNTBHUGY0NY B.U.G. Rating IC Rated CA T20 / T24 Rationale California Status Title 20 / 24 Status California Prop 65 RoHS Compliant Yes Wet Wet Under Medical Status Ves T20 Exempt - Fixtures Not Regulated Lawful for sale in California Lawful for sale Lead RoHS Compliant Yes FCC Compliant Yes	Compliance	
UL Application Energy Star No DLC Approved Yes DLC ID PLNTBHUGY0NY B.U.G. Rating IC Rated CA T20 / T24 Rationale California Status Title 20 / 24 Status California Prop 65 RoHS Compliant Culdor Control Culdor Control Con	Safety Listing	cULus - Listed
Energy Star DLC Approved Yes DLC ID PLNTBHUGY0NY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale California Status Title 20 / 24 Status California Prop 65 ROHS Compliant Yes No PLNTBHUGY0NY B1-U3-G1 T20 Exempt - Fixtures Not Regulated Lawful for sale in California Lawful for sale Lead ROHS Compliant Yes FCC Compliant	Location Rating	Wet
DLC Approved PLNTBHUGY0NY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale California Status California Status Lawful for sale in California Title 20 / 24 Status California Prop 65 RoHS Compliant Yes FCC Compliant Yes	UL Application	Outdoor
DLC ID PLNTBHUGY0NY B.U.G. Rating B1-U3-G1 IC Rated Yes CA T20 / T24 Rationale California Status California Status Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	Energy Star	No
B.U.G. Rating IC Rated Yes CA T20 / T24 Rationale California Status Title 20 / 24 Status California Prop 65 RoHS Compliant Yes FCC Compliant B1-U3-G1 Yes T20 Exempt - Fixtures Not Regulated Lawful for sale in California Lawful for sale Lead Yes FCC Compliant Yes	DLC Approved	Yes
IC Rated Yes CA T20 / T24 Rationale T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	DLC ID	PLNTBHUGY0NY
CA T20 / T24 Rationale California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	B.U.G. Rating	B1-U3-G1
California Status California Status Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	IC Rated	Yes
Title 20 / 24 Status California Prop 65 RoHS Compliant FCC Compliant Lawful for sale Lead Yes Yes	CA T20 / T24 Rationale	•
California Prop 65 RoHS Compliant Yes FCC Compliant Yes	California Status	Lawful for sale in California
RoHS Compliant Yes FCC Compliant Yes	Title 20 / 24 Status	Lawful for sale
FCC Compliant Yes	California Prop 65	Lead
	RoHS Compliant	Yes
SDS Sheet LED_Fixture	FCC Compliant	Yes
	SDS Sheet	LED_Fixture

Additional Information	
Additional Information	UV stabilized powder coated finish
Warranty	5 Year Limited - Fixtures

All Rights Reserved

https://www.satco.com/



