SATCO' NUVO

Project Name

Prepared By



NUVO 65-637 LED WIDE BEAM ANGLE CANOPY

Notes

Status	Active
Fixture Type	Canopy
Finish	Bronze
Wattage	60W/75W/90W
Lumen Output	7920L-12557L
CCT (Kelvin)	3000K/4000K/5000K
IP Rating	IP65
Indoor or Outdoor Fixture	Outdoor
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Specifications	
Technology	LED
Color Temperature	Warm White to Natural Light
CRI	80+
	120V-277V
Voltage Roam Anglo	
Beam Angle	190
Rated Hours	50000
Operating Temperature	-40C (-40F) to +50C (+122F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming
Photocell or Sensor	Optional Add-On
Lens Material	Polycarbonate (PC)
Surge Protection	Built-in surge protection - 6KV
Weight (lb.)	5.06
Material	Die-Cast Aluminum
Dimensions	
Height (in.)	3.62
Width (in.)	9.57
Length (in.)	9.57
-	
Compliance	
Safety Listing	cULus - Certified
Location Rating	Wet
DLC Approved	Yes
DLC ID	S-7KZD81
B.U.G. Rating	B3-U4-G5
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class A
SDS Sheet	LED_Fixture
Additional Information	
Additional Information	Recommended Mounting Height: 15 to 20 Fe
Specification Note	Multiple half-inch knockouts; Three quarter inch back knockout for pendant applications
Installation Notes	Hinged door for ease of installation
Integrated Features	Integrated DC Sensor Port
Warranty	5-Years

