SATCO NUVO

Project Name

ocation Prepared By



NUVO 65-662

LED GOOSENECK BRONZE FINISH

Notes

w1 07-02-2025 00:53:

Status	Active	
Finish	Bronze	
Wattage	30W/40W/50W	
Style	Traditional	
CCT (Kelvin)	3000K/4000K/5000K	
Color Temperature	Warm to Cool White	
Width (in.)	14.17	
Height (in.)	14.96	
Extension (in.)	23.23	
Indoor or Outdoor Fixture	Outdoor	

Smart Product Info	
IOT Enabled	No
Integrated Camera	No

Specifications	
Technology	LED
CRI	80+
Lumen Output	3300L-5500L
Rated Hours	50000
Voltage	120V-277V
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming
Photocell or Sensor	Has Photocell
Weight (lb.)	4.4
Fixture Material	Die-Cast Aluminum
Fixture Type	Gooseneck
Operating Temperature	-30C (-22F) to +50C (+122F)

Dimensions	
Back Plate or Canopy Diameter (in.)	4.65

Compliance	
Safety Listing	cULus - Listed; cULus - Certified; cETLus - Listed
Location Rating	Wet
ENERGY STAR	No
DLC Approved	Yes
DLC ID	S-85IVYA
ADA Compliant	No
B.U.G. Rating	B2-U2-G0
Dark Sky Compliant	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class A
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	UV Powder Coated Finish
Specification Note	For International Dark Sky compliance, the fixture CCT must be set to 3000K and installed in a downward facing and locked position.
Includes	16 Inch Mounting Arm
Warranty	5-Years

