

Project Name

Location Prepared By



## Notes

Status	Active	
Fixture Type	Strip Light	
Finish	White	
Wattage	30W/40W/50W	
Lumen Output	3900L-6750L	
CCT (Kelvin)	3500K/4000K/5000K	
IP Rating	IP20	
Indoor or Outdoor Fixture	Indoor	

Smart Product Info		
IOT Enabled	No	
Integrated Camera	No	

Technology	LED
Color Temperature	Neutral White to Daylight
CRI	80+
Voltage	120V-277V
Beam Angle	120
Rated Hours	50000
Operating Temperature	-20C (-4F) to +60C (+140F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming; Bi-Level Dimmable
Photocell or Sensor	Has Photocell
Lens Material	Polycarbonate (PC)
Surge Protection	Built-in surge protection - 2KV
Weight (lb.)	4.41
Material	Steel

Dimensions	
Height (in.)	3.27
Width (in.)	2.95
Length (in.)	48
Back Plate or Canopy Diameter (in.)	4.75

Compliance	
Safety Listing	cETLus - Listed; cULus - Listed
Location Rating	Damp
ENERGY STAR	No
DLC Approved	Yes
DLC ID	S-XSNARP; S-UZ1QD6; S-LL4W5Z
B.U.G. Rating	B2-U4-G2
NSF Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class A
Flicker Free	Yes
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	EM Mode 4W/90 Min run time. Other DLC Listings: S-UZ1QD6, Standard, Direct Linear Ambient Luminaires.
Warranty	5-Years