

Project Name

Location

Prepared By



Notes

(www) 18-17-0025 01-20-19

| General | |
|---------------------------|-------------------|
| Status | Active |
| Fixture Type | Strip Light |
| Finish | White |
| Wattage | 30W/40W/50W |
| Lumen Output | 3900L-6750L |
| CCT (Kelvin) | 3500K/4000K/5000K |
| IP Rating | IP20 |
| Indoor or Outdoor Fixture | Indoor |

| Smart Product Info | |
|--------------------|----|
| IOT Enabled | No |
| Integrated Camera | No |

| Specifications | |
|------------------------|---------------------------------|
| Technology | LED |
| Color Temperature | Warm to Cool White |
| CRI | 80+ |
| Voltage | 120V-277V |
| Beam Angle | 120 |
| Rated Hours | 50000 |
| Operating Temperature | -20C (-4F) to +60C (+140F) |
| Dimmable | Yes-Dimmable |
| Dimming Note | 0-10V Dimming Only |
| Photocell or Sensor | Optional Add-On |
| Lens Material | Polycarbonate (PC) |
| Surge Protection | Built-in surge protection - 2KV |
| Max. Connectable Units | 10 |
| Weight (lb.) | 6.84 |
| Material | Steel |

| Dimensions | |
|-------------------------------------|------|
| Height (in.) | 3.27 |
| Width (in.) | 2.95 |
| Length (in.) | 96 |
| Back Plate or Canopy Diameter (in.) | 4.75 |

| Compliance | |
|----------------------------|----------------------------------|
| Safety Listing | cULus - Certified |
| Location Rating | Damp |
| UL Application | Ceiling / Wall |
| ENERGY STAR | No |
| DLC Approved | Yes |
| DLC ID | P4B87ZHS; PLIHZ3V2CRB9; S-04FYBP |
| B.U.G. Rating | B2-U4-G2 |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| Canadian Standard ICES-005 | Class A |
| Flicker Free | Yes |
| SDS Sheet | LED_Fixture |

| Additional Information | |
|------------------------|---|
| Installation Notes | Maximum connected units is 10. If dimming, the dimmer max load will dictate how many units can be on the run/control. |
| Warranty | 5-Years |