

Project Name

Location

Prepared By



Notes

[www] 03-19-2023 01-03-01

General	
Status	Transitioning
Substitute	65-703R1
Fixture Type	Strip Light
Finish	White
Wattage	82W
Lumen Output	10400L-10800L
CCT (Kelvin)	3500K/4000K/5000K
IP Rating	IP20
Indoor or Outdoor Fixture	Indoor

Smart Product Info	
IOT Enabled	No

Specifications	
Technology	LED
Color Temperature	Neutral White to Daylight
CRI	80+
Voltage	120V-347V
Beam Angle	120
Rated Hours	50000
Operating Temperature	-20C (-4F) to +60C (+140F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming Only
Photocell or Sensor	Optional Add-On
Lens Material	Polycarbonate (PC)
Surge Protection	Built-in surge protection - 3KV
Weight (lb.)	6.84
Material	Steel

Dimensions	
Height (in.)	3.27
Width (in.)	2.95
Length (in.)	96
Back Plate or Canopy Diameter (in.)	4.75

Compliance	
Safety Listing	cULus - Listed
Location Rating	Damp
UL Application	Ceiling / Wall
Energy Star	No
DLC Approved	Yes
DLC ID	PLRLXXEMUEOR; PLTRVDFB3IUR
B.U.G. Rating	B3-U4-G3
NSF Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Flicker Free	Yes
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	Other DLC Listings: PLTRVDFB3IUR, Standard, Direct Linear Ambient Luminaires.
Specification Note	Add on sensors, 86-202 and 86-211, are only rated for 120-277 Volt
Installation Notes	Maximum connected units are 7. If dimming, the dimmer max load will dictate how many units can be on the run/control.
Warranty	5 Year Limited - Fixtures