SATCO' NUVO

Project Name

Location

Prepared By



NUVO	65-964
LED 80W UFO W/PLUG/120V	

Notes

Fixture TypeShop LightFinishBlackWattage80WWattage80WLumen Output9071LCCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndor; OutdoorSmart Product InfoUTenabledNoSpecificationsEDCool WhiteCool WhiteColor TemperatureCool WhiteColor TemperatureCool WhiteColor Temperature2000Operating Temperature30000Operating Temperature200C (-4F) to +45C (+113F)DimmableNon-DimmableNon-DimmableSpecification - 2KVWeight (lb.)1.61MaterialDile-Cast AluminumDimensionsEutomic Coll fieldLocation RatingWidth (in.)5.63Safety ListingCULus - CertifieldLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaCalifornia StatusKesCompliantYesCaconpliant Standard ICES-005LeadCompliantYesCanadian Standard ICES-005LeadSp SheetElE/ FixtureAdditional InformationSpecification NoteSp StatusBark Powder Coating Finis	General	
FinishBlackWattage80WLumen Output9071LCCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSmart Product InfoIOT EnabledNoSpecificationsSpecificationsColor TemperatureCool WhiteColor TemperatureCool WhiteCRI80+4OutpointBott Colspan="2">SpecificationsCool WhiteCool (AF) to +45C (+113F)DimeableNoSurge ProtectionBuilt-in surge protection - 2KVWeight	Status	Active
Wattage80WLumen Output9071LCCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSmart Product InfoNoStart Product InfoStart Product InfoNoStart Product InfoStart Product Produ	Fixture Type	Shop Light
Lumen Output9071LCCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSmart Product InfoNoSomart Product InfoNoSpecificationsEEDColor TemperatureCool WhiteColor TemperatureCool WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature20C (4F) to +45C (+113F)DinmableNon-DinmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (Ib.)1.61DimensionsScatalHeight (in.)5.63Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRAty J 24 StatusLawful for saleCalifornia Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationYesSpecification NoteBlack Powder Coating FinishIncludesLocking Snap Hook	Finish	Black
CCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSmart Product InfoIntegrated CameraIOT EnabledNoSpecificationsEDStart Product InfoIEDSpecificationsColor WhiteColor TemperatureCool WhiteColor TemperatureCool WhiteCRI80+Voltage100Beam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DinmableNon-DinmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions	Wattage	80W
IP Rating IP65 Indoor or Outdoor Fixture Indoor; Outdoor Smart Product Info Integrated Camera IOT Enabled No Integrated Camera No Specifications ED Color Temperature Cool White CRI 80+ Voltage 100 Beam Angle 110 Rated Hours 30000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (Ib.) 1.61 Material Die-Cast Aluminum Dimensions Sci3 Height (in.) 5.63 Width (in.) 8.27 Compliance Sci4 Safety Listing CULus - Certified Location Rating B3-U2-G1 California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Frop 65 Lead RohS Compliant Yes Candian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Yes Spos Sheet Black Powde	Lumen Output	9071L
Indoor or Outdoor Fixture Indoor; Outdoor Smart Product Info IOT Enabled No Integrated Camera No Specifications Technology LED Color Temperature Cool White CRI 80+ Voltage 120V Beam Angle 110 Rated Hours 30000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-In surge protection - 2KV Weight (Ib.) 1.61 Material Die-Cast Aluminum Dimensions Height (In.) 5.63 Safety Listing CULus - Certified Location Rating Wet DLC Approved No B.U.G. Rating B3-U2-G1 California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS COMPILATION SDES FOC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Specification Note Black Powder Coating Finish Includes Locking Snap Hook	CCT (Kelvin)	4000K
Smart Product InfoIOT EnabledNoIntegrated CameraNoSpecificationsEEDTechnologyCool WhiteColor TemperatureCool WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNo-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions	IP Rating	IP65
NoIntegrated CameraNoSpecificationsLEDTechnologyLEDColor TemperatureCool WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DinmableNon-DinmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsScaWeight (in.)5.63Width (in.)8.27ComplianceSurge ProtectionSafety Listingcullus - CertifiedLocation RatingWetDLC ApprovedNoB.J.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantY	Indoor or Outdoor Fixture	Indoor; Outdoor
Integrated CameraNoSpecificationsTechnologyLEDColor TemperatureCool WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions	Smart Product Info	
Specifications Technology LED Color Temperature Cool White CRI 80 + Voltage 120V Beam Angle 110 Rated Hours 30000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (Ib.) 1.61 Material Die-Cast Aluminum Dimensions E Protection 8.27 Compliance E Safety Listing CULus - Certified Location Rating Wet DLC Approved No B.U.G. Rating Eavful for sale in California California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Standard ICES-005 Class A SDS Sheet LBC_Fixture Additional Information Elack Powder Coating Finish <	IOT Enabled	No
TechnologyLEDColor TemperatureCool WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableDimmablePolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsS.63Width (in.)5.63Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingBal-U2-G1California StatusLawful for sale in CaliforniaCilifornia StatusLawful for saleCompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantSlas ASpecification NoteBlack Powder Coating FinishIncludesLaving Snap Hook	Integrated Camera	No
Color TemperatureCool WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DinmableNon-DinmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)Safety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRotS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetELD_FixtureAdditional InformationSpecification NoteBlack Powder Coating FinishIncludesLocking Snap Hook	Specifications	
Color TemperatureCool WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DinmableNon-DinmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)Safety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRotS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetELD_FixtureAdditional InformationSpecification NoteBlack Powder Coating FinishIncludesLocking Snap Hook	Technology	LED
CRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)Safety Listing5.63KuttingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	Color Temperature	Cool White
Beam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCandian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationSlack Powder Coating FinishIncludesBlack Powder Coating Finish	CRI	80+
Beam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCandian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationSlack Powder Coating FinishIncludesBlack Powder Coating Finish	Voltage	120V
Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook		110
Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	-	30000
DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishSpecification NoteBlack Powder Coating FinishIncludesLocking Snap Hook		-20C (-4F) to +45C (+113F)
Lens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYesCC CompliantClass ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	Dimmable	
Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions5.63Width (in.)5.63Width (in.)8.27ComplianceCULus - CertifiedSafety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLeadRoHS CompliantYesFCC CompliantSes ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	Lens Material	Polycarbonate (PC)
Weight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	Surge Protection	
DimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYesCC CompliantClass ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	Weight (lb.)	
Height (in.)5.63Width (in.)8.27ComplianceCulus - CertifiedSafety Listingculus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishSpecification NoteBlack Powder Coating FinishIncludesLocking Snap Hook	Material	Die-Cast Aluminum
Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	Dimensions	
ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	Height (in.)	5.63
Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantClass ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	Width (in.)	8.27
Jocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantClass ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	Compliance	
DLC Approved No B.U.G. Rating B3-U2-G1 California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Black Powder Coating Finish Includes Locking Snap Hook	Safety Listing	cULus - Certified
DLC Approved No B.U.G. Rating B3-U2-G1 California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Black Powder Coating Finish Includes Locking Snap Hook	Location Rating	Wet
California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationBlack Powder Coating FinishIncludesLocking Snap Hook	DLC Approved	No
Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Black Powder Coating Finish Includes Locking Snap Hook	B.U.G. Rating	B3-U2-G1
California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Specification Note Black Powder Coating Finish Includes Locking Snap Hook	California Status	Lawful for sale in California
RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Specification Note Black Powder Coating Finish Includes	Title 20 / 24 Status	Lawful for sale
RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Specification Note Black Powder Coating Finish Includes	California Prop 65	Lead
FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Specification Note Specification Note Black Powder Coating Finish Includes Locking Snap Hook	RoHS Compliant	
Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Specification Note Black Powder Coating Finish Includes Locking Snap Hook	FCC Compliant	
SDS Sheet LED_Fixture Additional Information Specification Note Black Powder Coating Finish Includes Locking Snap Hook	Canadian Standard ICES-005	Class A
Specification Note Black Powder Coating Finish Includes Locking Snap Hook	SDS Sheet	LED_Fixture
Includes Locking Snap Hook	Additional Information	
Includes Locking Snap Hook	Specification Note	Black Powder Coating Finish
	Includes	
	Warranty	

