SATCO' NUVO

Project Name

Location

Prepared By



NUVO 65-985 LED ENTRYWAY WALL PACK

Notes

Active Wall Pack Black 10W/15W/20W 1410L-2839L 3000K/4000K/5000K Soft White to Natural Light IP65 Outdoor LED 80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV 2.64
Black 10W/15W/20W 1410L-2839L 3000K/4000K/5000K Soft White to Natural Light IP65 Outdoor LED 80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
10W/15W/20W 1410L-2839L 3000K/4000K/5000K Soft White to Natural Light IP65 Outdoor LED 80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
1410L-2839L 3000K/4000K/5000K Soft White to Natural Light IP65 Outdoor LED 80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
3000K/4000K/5000K Soft White to Natural Light IP65 Outdoor LED 80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
Soft White to Natural Light IP65 Outdoor LED 80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
IP65 Outdoor LED 80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
Outdoor LED 80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
LED 80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
80+ 120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
120V-347V 100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
100 50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
50000 -40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
-40C (-40F) to +50C (+122F) Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
Yes-Dimmable 0-10V Dimming Only Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
Has Photocell Polycarbonate (PC) Built-in surge protection - 2.5KV
Built-in surge protection - 2.5KV
2.64
Die-Cast Aluminum
10.96
6.86
4.53
cULus
Wet
Yes
S-BXPL7Q
No
B1-U3-G1
Lawful for sale in California
Lawful for sale
Lead
Yes
Yes
Class B
No
LED_Fixture
Powder Coated
Type III Light Distribution; Photocell does not
function in artificial light 5-Years

