SATCO NUVO

Project Name

Prepared By



EL EXIT SIGN - SF GR CLR

Notes

General	
Status	Active
Fixture Type	Exit Sign
Finish	Clear
Wattage	2.94W
Indoor or Outdoor Fixture	Indoor

	maco:	
Specifications		
Technology	LED	
Voltage	120V/277V	
Operating Temperature	+10C (+50F) to +40C (+104F)	
Dimmable	Non-Dimmable	
Surge Protection	Built-in surge protection - 3KV	
Weight (lb.)	2.76	
Material	Aluminum	
Dimensions		
Height (in.)	9.69	
Width (in.)	12.06	
Length (in.)	1.81	

Compliance	
Safety Listing	ULus - Certified; ULus - Listed
Location Rating	Damp
ENERGY STAR	No
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	Input Wattage: 2.94W; Output Wattage: 0.5W; Energy Used in Maintenance Mode: 2.94W
Specification Note	Aluminum, Acrylic Panel, 4.8V AA300mAh Ni- Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 6 in.; Letter Stroke: 0.75 in.
Includes	Mounting hardware and accessories
Warranty	2-Years