SATCO NUVO

Project Name

ocation

Prepared By



NUVO 67-114

REC EL EXIT SIGN - SF RD CLR

Notes

General	
Status	Active
Fixture Type	Exit Sign
Finish	Clear
Wattage	3.14W
Indoor or Outdoor Fixture	Indoor

Specifications	
Technology	LED
Voltage	120V/277V
Operating Temperature	+10C (+50F) to +40C (+104F)
Dimmable	Non-Dimmable
Lens Material	Acrylic
Surge Protection	Built-in surge protection - 3KV
Weight (lb.)	5.2
Material	Aluminum

Dimensions	
Height (in.)	11
Width (in.)	15.75
Length (in.)	4

Compliance	
Safety Listing	ULus - Certified; ULus - Listed
Location Rating	Damp
ENERGY STAR	No
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	Input Wattage: 3.14W; Output Wattage: 0.5W; Energy Used in Maintenance Mode: 3.14W
Specification Note	Aluminum, Acrylic Panel, 4.8V AA300mAh Ni- Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 6 in.; Letter Stroke: 0.75 in.
Includes	Mounting hardware and accessories
Warranty	2-Years