SATCO NUVO

Project Name

ocation

Prepared By



NUVO 67-116

REC EL EXIT SIGN - SF GR CLR

Notes

| General | |
|---------------------------|-----------|
| Status | Active |
| Fixture Type | Exit Sign |
| Finish | Clear |
| Wattage | 2.94W |
| Indoor or Outdoor Fixture | Indoor |

| Specifications | |
|-----------------------|---------------------------------|
| Technology | LED |
| Voltage | 120V/277V |
| Operating Temperature | +10C (+50F) to +40C (+104F) |
| Dimmable | Non-Dimmable |
| Lens Material | Acrylic |
| Surge Protection | Built-in surge protection - 3KV |
| Weight (lb.) | 5.2 |
| Material | Aluminum |

| Dimensions | |
|--------------|-------|
| Height (in.) | 11 |
| Width (in.) | 15.75 |
| Length (in.) | 4 |

| Compliance | |
|----------------------|---------------------------------|
| Safety Listing | ULus - Certified; ULus - Listed |
| Location Rating | Damp |
| ENERGY STAR | No |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Fixture |

| Additional Information | |
|-------------------------------|---|
| Additional Information | Input Wattage: 2.94W; Output Wattage: 0.4W; Energy Used in Maintenance Mode: 2.94W |
| Specification Note | Aluminum, Acrylic Panel, 4.8V AA300mAh Ni- Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Lumens/Illuminance: 73cd/m2 average; Letter Height: 6 in.; Letter Stroke: 0.75 in. |
| Includes | Mounting hardware and accessories |
| Warranty | 2-Years |