## SATCO NUVO

Project Name

ocation Prepared By



**NUVO 67-123** 

EXIT/LIGHT DH - RED - NYC

Notes

Status	Active	
Fixture Type	Exit Sign	
Finish	White	
Wattage	3W	
Lumen Output	220L	
CCT (Kelvin)	5700K	
Indoor or Outdoor Fixture	Indoor	

Technology	LED
CRI	70+
Voltage	120V/277V
Operating Temperature	+10C (+50F) to +40C (+104F)
Dimmable	Non-Dimmable
Lens Material	Polycarbonate (PC)
Surge Protection	Built-in surge protection - 3KV
Weight (lb.)	6.28
Material	Steel

Height (in.)	14.88
Width (in.)	14.56
Length (in.)	2.31
Compliance	
Safety Listing	ULus - Certified; ULus - Listed

Safety Listing	ULus - Certified; ULus - Listed
Location Rating	Damp
ENERGY STAR	No
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	No
Canadian Standard ICES-005	Class B
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	Input Wattage: 3.0W; Output Wattage: 1.6W; Energy Used in Maintenance Mode: 3.0W
Specification Note	20-gauge Steel, 3.6V AA600mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 8 in.; Letter Stroke: 1 in.; Path of Egress: 6 Ft.
Includes	Mounting hardware and accessories
Warranty	2-Years

