## SATCO NUVO

Project Name

ocation Pre

Prepared By



**NUVO 67-124** 

EXIT/LIGHT TH - RED - NYC

Notes

| General                   |           |  |
|---------------------------|-----------|--|
| Status                    | Active    |  |
| Fixture Type              | Exit Sign |  |
| Finish                    | White     |  |
| Wattage                   | 3W        |  |
| Lumen Output              | 330L      |  |
| CCT (Kelvin)              | 5700K     |  |
| Indoor or Outdoor Fixture | Indoor    |  |

| Specifications        |                                 |  |
|-----------------------|---------------------------------|--|
| Technology            | LED                             |  |
| CRI                   | 70+                             |  |
| Voltage               | 120V/277V                       |  |
| Operating Temperature | +10C (+50F) to +40C (+104F)     |  |
| Dimmable              | Non-Dimmable                    |  |
| Lens Material         | Polycarbonate (PC)              |  |
| Surge Protection      | Built-in surge protection - 3KV |  |
| Weight (lb.)          | 6.61                            |  |
| Material              | Steel                           |  |
| Dimensions            |                                 |  |

| Dimensions   |       |
|--------------|-------|
| Height (in.) | 14.88 |
| Width (in.)  | 14.56 |
| Length (in.) | 2.31  |

| Compliance                 |                                 |
|----------------------------|---------------------------------|
| Safety Listing             | ULus - Certified; ULus - Listed |
| Location Rating            | Damp                            |
| ENERGY STAR                | No                              |
| DLC Approved               | No                              |
| California Status          | Lawful for sale in California   |
| Title 20 / 24 Status       | Lawful for sale                 |
| California Prop 65         | Lead                            |
| RoHS Compliant             | Yes                             |
| FCC Compliant              | No                              |
| Canadian Standard ICES-005 | Class B                         |
| SDS Sheet                  | LED_Fixture                     |

| Additional Information |   |
|------------------------|---|
| Additional Information | Input Wattage: 3.0W; Output Wattage: 1.6W;<br>Energy Used in Maintenance Mode: 3.0W   |
| Specification Note     | 20-gauge Steel, 3.6V AA800mAh Ni-Cad<br>Battery, 90 minutes duration, 24 hour charge<br>time, 10C-40C; Letter Height: 8 in.; Letter<br>Stroke: 1 in.; Path of Egress: 6 Ft. |
| Includes               | Mounting hardware and accessories   |
| Warranty               | 2-Years   |

