SATCO NUVO

Project Name

ocation Prepared By



NUVO 67-130

EMERG LIGHT DH

Notes

| General | | |
|---------------------------|-----------------|--|
| Status | Active | |
| Fixture Type | Emergency Light | |
| Finish | White | |
| Wattage | 0.8W | |
| Lumen Output | 210L | |
| CCT (Kelvin) | 5700K | |
| Indoor or Outdoor Fixture | Indoor | |

| Specifications | |
|-----------------------|---------------------------------|
| Technology | LED |
| CRI | 70+ |
| Voltage | 120V/277V |
| Operating Temperature | +10C (+50F) to +40C (+104F) |
| Dimmable | Non-Dimmable |
| Lens Material | Polycarbonate (PC) |
| Surge Protection | Built-in surge protection - 3KV |
| Weight (lb.) | 1.07 |
| Material | Thermoplastic |
| Dimensions | |
| Height (in.) | 4.5 |
| Width (in.) | 12.5 |
| Length (in.) | 2.88 |

| Compliance | | |
|----------------------|-----------------------------------|--|
| Safety Listing | cULus - Certified; cULus - Listed | |
| Location Rating | Damp | |
| UL Application | Unit equipment | |
| ENERGY STAR | No | |
| DLC Approved | No | |
| California Status | Lawful for sale in California | |
| Title 20 / 24 Status | Lawful for sale | |
| California Prop 65 | Lead | |
| RoHS Compliant | Yes | |
| FCC Compliant | Yes | |
| SDS Sheet | LED_Fixture | |

| Additional Information | | |
|------------------------|--|--|
| Additional Information | Input Wattage: 0.8W; Output Wattage: 2W; Energy Used in Maintenance Mode: 0.8W | |
| Specification Note | UL94V-0, Thermoplastic, 3.6V AA1000mAh Ni- Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Path of Egress: 6 Ft. | |
| Includes | Mounting hardware and accessories | |
| Warranty | 2-Years | |

