

Project Name

Location

Prepared By



# SATCO 67-580

EM LIGHT-CAN-WET

## Notes

[www] 18-27-2023 05:20:49

## General

|                           |                    |
|---------------------------|--------------------|
| Status                    | Active             |
| Fixture Type              | Emergency Light    |
| Finish                    | White              |
| Wattage                   | 3.5W               |
| Lumen Output              | 600L               |
| CCT (Kelvin)              | 5000K              |
| Temperature               | Natural Light      |
| IP Rating                 | IP65               |
| Indoor or Outdoor Fixture | Indoor and Outdoor |

## Specifications

|                       |                                 |
|-----------------------|---------------------------------|
| Technology            | LED                             |
| CRI                   | 80+                             |
| Voltage               | 120V-347V                       |
| Operating Temperature | 0C (+32F) to +50C (+122F)       |
| Dimmable              | Non-Dimmable                    |
| Lens Material         | Polycarbonate (PC)              |
| Surge Protection      | Built-in surge protection - 6KV |
| Weight (lb.)          | 2.2                             |
| Material              | Thermoplastic                   |

## Compliance

|                            |               |
|----------------------------|---------------|
| Safety Listing             | CSAus         |
| Location Rating            | Wet           |
| California Status          | Non-Compliant |
| Title 20 / 24 Status       | Non-Compliant |
| California Prop 65         | Lead          |
| RoHS Compliant             | Yes           |
| FCC Compliant              | Yes           |
| Canadian Standard ICES-005 | Class B       |
| SDS Sheet                  | LED_Fixture   |

## Additional Information

|                    |                                                                  |
|--------------------|------------------------------------------------------------------|
| Specification Note | Ni-Cad Battery; 120 minute discharge time; 24 Hour Recharge Time |
| Warranty           | 2-Years                                                          |