SATCO NUVO

Project Name

ocation Prepared By



Notes

ww] 11-20-2024 00:06:

General Active Watts 15W Incandescent Equivalent 90W Fluorescent Equivalent 23W Volts 120V Shape PAR3B Base Medium ANSI Base E26 Finish Clear CCT (Kelvin) 5000K Temperature Natural Light CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Electrical Operating Frequency 60Hz Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 16.5in. D x 17.5in. H Compliance		
Watts 15W Incandescent Equivalent 90W Fluorescent Equivalent 23W Volts 120V Shape PAR38 Base Medium ANSI Base E26 Finish Clear CCT (Kelvin) 5000K Temperature Natural Light CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Electrical Operating Frequency 60Hz Operating Temperature Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Material Thermo Plastic (PBT) Additional Information Installation Notes Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H <th>General</th> <th></th>	General	
Incandescent Equivalent	Status	Active
Fluorescent Equivalent 23W Volts 120V Shape PAR38 Base Medium ANSI Base E26 Finish Clear CCT (Kelvin) 5000K Temperature Natural Light CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Electrical Operating Frequency Operating Frequency 60Hz Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17.5in. H Compliance Safety Listing CULus - Listed Coation Rating Wet CA T20 / T24 Rationale Contai	Watts	15W
Volts 120V Shape PAR38 Base Medium ANSI Base E26 Finish Clear CCT (Kelvin) 5000K Temperature Natural Light CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Flectrical Operating Frequency 60Hz Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Material Thermo Plastic (PBT) Additional Information Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lenvel Lamvan (Lamvin) PAR3 Medium 4 Medium 4 Medium 4 Clear Lense	Incandescent Equivalent	90W
Shape PAR38 Base Medium ANSI Base E26 Finish Clear CCT (Kelvin) 5000K Temperature Natural Light CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Flectrical Operating Frequency 60Hz Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Fluorescent Equivalent	23W
Base Medium ANSI Base E26 Finish Clear CCT (Kelvin) 5000K Temperature Natural Light CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Electrical Operating Frequency 60Hz Power Factor 0.9 Operating Temperature 20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lensed Lensed Lamp Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Volts	120V
ANSI Base E26 Finish Clear CCT (Kelvin) 5000K Temperature Natural Light CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Flectrical Operating Frequency 60Hz Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Shape	PAR38
Finish Clear CCT (Kelvin) 5000K Temperature Natural Light CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Flectrical Operating Frequency Operating Temperature Operating Temperature Physical Lensed Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CCA T20 / T24 Rationale California Status Lawful for sale in California	Base	Medium
CCT (Kelvin) Temperature Natural Light QRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Flectrical Operating Frequency Operating Temperature Operating Temperature Physical Lens Elnish Lens Finish Clear Lens Material Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CA T20 / T24 Rationale California Status Lawful for sale in California	ANSI Base	E26
Temperature CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Electrical Operating Frequency Operating Temperature Operating Temperature Physical Lensed Lensed Lensed Lensed Lensed Lamp Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing Location Rating Wet CA T20 / T24 Rationale California Status Lawful for sale in California	Finish	Clear
CRI 90 Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Electrical Operating Frequency 60Hz Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Installation Notes 71in. D x 56.5in. H; Counter unit dimensions: 21.5in. W x 17in. D x 56.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	CCT (Kelvin)	5000K
Lumens 1200L Beam Spread 40 Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Electrical Operating Frequency 60Hz Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Temperature	Natural Light
Beam Spread Dimmable Yes-Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Electrical Operating Frequency Operating Frequency Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Installation Notes Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing Location Rating Wet CA T20 / T24 Rationale California Status Lawful for sale in California	CRI	90
Dimmable Yes-Dimmable Hours Rated 25000 Product Category PAR Technology LED Electrical Operating Frequency 60Hz Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Installation Notes 17in. D x 56.5in. H; Counter unit dimensions: 21.5in. W x 17in. D x 56.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Lumens	1200L
Hours Rated Product Category PAR Technology Electrical Operating Frequency Operating Temperature Operating Temperature Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale California Status LED 60Hz Cental California Compliance Contains T20 Listed Item S29449 California Status California	Beam Spread	40
Product Category Technology Electrical Operating Frequency Operating Temperature Lensed Lensed Lamp Lense Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale California Status Lawful for sale in California	Dimmable	Yes-Dimmable
Technology Electrical Operating Frequency 60Hz Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale California Status Lawful for sale in California	Hours Rated	25000
Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Installation Notes Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Product Category	PAR
Operating Frequency Power Factor Operating Temperature Operating Temperature Operating Temperature Lensed Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale California Status Lawful for sale in California	Technology	LED
Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Installation Notes Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Electrical	
Operating Temperature -20C (-4F) to +45C (+113F) Physical Lensed Lensed Lamp Lens Finish Clear Thermo Plastic (PBT) Additional Information Installation Notes Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale California Status Lawful for sale in California	Operating Frequency	60Hz
Lensed Lensed Lamp Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Installation Notes Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Power Factor	0.9
Lensed Lensed Lamp Lens Finish Clear Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale California Status Lawful for sale in California	Operating Temperature	-20C (-4F) to +45C (+113F)
Lens Finish Clear Lens Material Thermo Plastic (PBT) Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale California Status Clear Clear Clear Clear Clear Coutine Plastic (PBT)	Physical	
Lens Material Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale California Status Character (PBT) Floor display overall dimensions: 21.5in. W x 17in. D x 17in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Contains T20 Listed Item S29449 California Status	Lensed	Lensed Lamp
Additional Information Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Lens Finish	Clear
Floor display overall dimensions: 21.5in. W x 17in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing	Lens Material	Thermo Plastic (PBT)
Installation Notes 217in. D x 56.5in. H; Counter unit dimensions: 21in. W x 16.5in. D x 17.5in. H Compliance Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Additional Information	
Safety Listing CULus - Listed Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Installation Notes	17in. D x 56.5in. H; Counter unit dimensions:
Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Compliance	
Location Rating Wet CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California	Safety Listing	cULus - Listed
CA T20 / T24 Rationale Contains T20 Listed Item S29449 California Status Lawful for sale in California		
California Status Lawful for sale in California		Contains T20 Listed Item S29449
		Lawful for sale in California