## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO S11271**

5.5MR16/GU10/RGB/TW/SF

Notes

General	
Status	Active
Watts	5.5W
Incandescent Equivalent	50W
Volts	120V
Shape	MR16
Base	Bi Pin GU10
ANSI Base	GU10
Finish	Clear
CCT (Kelvin)	2700K-5000K
Temperature	Warm to Cool White/Color Changeable
CRI	80
Lumens	400L
Beam Spread	50
Dimmable	Yes-Dimmable
Hours Rated	25000
Lamp Type	MR
Technology	LED
Smart Product Info	
IOT Enabled	Yes
Operational Humidity	10% - 85% R.H.
Number of Switching Cycles	12500
Software Upgradeable	Yes
Communication Protocol	WiFi
Voice Assistants Supported	Siri; Alexa; Hey Google; SmartThings
Software Supported	Tuya/Starfish APP
Electrical	
Operating Frequency	60Hz
Specifications	
Dimming Type	Smart Starfish Ann anly
Dimming Type	Smart-Starfish App only Only with Starfish App
Dimming Note	Only with Starfish App
Dimming Note Power Factor	Only with Starfish App 0.7
Dimming Note Power Factor Operating Position	Only with Starfish App 0.7 Universal
Dimming Note Power Factor Operating Position Operating Temperature	Only with Starfish App 0.7
Dimming Note Power Factor Operating Position	Only with Starfish App 0.7 Universal
Dimming Note Power Factor Operating Position Operating Temperature	Only with Starfish App 0.7 Universal
Dimming Note Power Factor Operating Position Operating Temperature Physical	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)
Dimming Note Power Factor Operating Position Operating Temperature Physical MOL	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97
Dimming Note Power Factor Operating Position Operating Temperature Physical MOL MOD	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.2
Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.2 White
Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color Lens Finish	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.2 White Clear
Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish  Lens Material	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.2 White Clear Plastic (PS)
Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color Lens Finish Lens Material Weight (lb.)	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.2 White Clear Plastic (PS)
Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color Lens Finish Lens Material Weight (lb.)  Additional Information	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.2 White Clear Plastic (PS) 0.08
Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish  Lens Material  Weight (lb.)  Additional Information  Rated For Enclosed Fixture	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.2 White Clear Plastic (PS) 0.08
Dimming Note Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Lens Finish  Lens Material  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty	Only with Starfish App 0.7 Universal -20C (-4F) to +45C (+113F)  1.97 2.2 White Clear Plastic (PS) 0.08

Location Rating	Damp
Energy Star	Yes
ES Unique ID	ESID-2368910
CA T20 / T24 Rationale	Non-Compliant - <82 CRI
California Status	Non-Compliant
Title 20 / 24 Status	Non-Compliant
California Compliant Substitute	S11278
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="https://www.satco.com/">https://www.satco.com/</a>



