## SATCO NUVO

Project Name

ocation Prepared By



Notes

ww] 10-27-2025 05:20:4

General	
Status	Active
Watts	4W
Incandescent Equivalent	40W
Volts	120V
Shape	CA11
Base	Candelabra
ANSI Base	E12
Finish	Satin Spun
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	300L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Operating Frequency	60Hz
Operating Frequency Power Factor	60Hz 0.9
Power Factor	0.9
Power Factor Operating Position	0.9 Universal
Power Factor Operating Position Operating Temperature	0.9 Universal
Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL	0.9 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL MOD	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56 Yes
Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56 Yes
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56  Yes 2-Years
Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56  Yes 2-Years
Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56  Yes 2-Years  CULus Damp
Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56  Yes 2-Years  CULus Damp Non-Compliant
Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status  Title 20 / 24 Status	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant
Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant Lawful for sale
Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	0.9 Universal -20C (-4F) to +45C (+113F)  4 1.38 None 0.56  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale Lawful for sale

Yes

LED\_Lamp



FCC Compliant

SDS Sheet