SATCO NUVO

Project Name

ocation Prepared By



Notes

4CA11/LED/SA/E12/27K/120V/CD

General	
	Antico
Status	Active
Watts	4W 40W
Incandescent Equivalent	· · · · · · · · · · · · · · · · · · ·
Volts	120V
Shape	CA11
Base	Candelabra
ANSI Base	E12
Finish CCT (Kelvin)	Satin Spun 2700K
	Warm White
Temperature CRI	80+
Lumens	300L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	15000
	Candle
Product Category Technology	LED
	LLD
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Operating Frequency	60Hz
Operating Frequency Power Factor	60Hz 0.9
Power Factor	0.9
Power Factor Operating Position	0.9 Universal
Power Factor Operating Position Operating Temperature	0.9 Universal
Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL MOD	0.9 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years CULus Damp
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years CULus Damp Non-Compliant
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years CULus Damp Non-Compliant Non-Compliant
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	0.9 Universal -20C (-4F) to +45C (+113F) 4 1.38 None 0.56 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale

Yes

LED_Lamp



FCC Compliant

SDS Sheet