SATCO NUVO

Project Name

Location Prepared By



SATCO S11376

4.5CFC/LED/930/120V/E12

Notes

www] 01-15-2024 02:40:0

General	
Status	Discontinued
Substitute	S21297
Watts	4.5W
Incandescent Equivalent	40W
Volts	120V
Shape	CA11
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	3000K
Temperature	Warm White
CRI	90
Lumens	360L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Lamp Type	Candle
Technology	LED
Electrical	
Operating Frequency	60Hz
Operating Frequency Power Factor	60Hz 0.7
Power Factor	0.7
Power Factor Operating Position	0.7 Universal
Power Factor Operating Position Operating Temperature	0.7 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical	0.7 Universal
Power Factor Operating Position Operating Temperature Physical MOL	0.7 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL MOD	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26 0.03
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26 0.03
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26 0.03
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26 0.03
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26 0.03 Yes 3 Year Limited
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26 0.03 Yes 3 Year Limited cULus Damp Yes
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star ES Unique ID	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26 0.03 Yes 3 Year Limited cULus Damp Yes ESID-2363793
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star ES Unique ID CA T20 / T24 Rationale	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26 0.03 Yes 3 Year Limited cULus Damp Yes ESID-2363793 T20 Listed
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star ES Unique ID	0.7 Universal -20C (-4F) to +45C (+113F) 3.9 1.26 0.03 Yes 3 Year Limited cULus Damp Yes ESID-2363793

Safety Listing	cULus
Location Rating	Damp
Energy Star	Yes
ES Unique ID	ESID-2363793
CA T20 / T24 Rationale	T20 Listed
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
SDS Sheet	LED Lamp