

Project Name

Location

Prepared By



SATCO S11445

12A19/PIR/930/120V/ND

Notes

(www) 09-04-2023 01:10:43

General

| | |
|-------------------------|----------------|
| Status | Active |
| Watts | 12W |
| Incandescent Equivalent | 75W |
| Volts | 120V |
| Shape | A19 |
| Base | Medium |
| ANSI Base | E26 |
| Finish | Frost |
| CCT (Kelvin) | 3000K |
| Temperature | Soft White |
| CRI | 90+ |
| Lumens | 1050L |
| Beam Spread | 230 |
| Dimmable | Non-Dimmable |
| Hours Rated | 15000 |
| Photocell or Sensor | Has PIR Sensor |
| Product Category | Type A |
| Technology | LED |

Electrical

| | |
|-----------------------|----------------------------|
| Operating Frequency | 60Hz |
| Power Factor | 0.7 |
| Operating Temperature | -20C (-4F) to +40C (+104F) |

Physical

| | |
|---------------|-------|
| MOL | 5.11 |
| MOD | 2.36 |
| Housing Color | White |
| Weight (lb.) | 0.27 |

Additional Information

| | |
|----------------------------|--|
| Additional Info | The lamp has an integrated motion-activated sensor designed to activate between dusk and dawn. It remains inactive in the absence of motion but turns on for a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb. |
| Rated For Enclosed Fixture | No |
| Installation Notes | To achieve optimal sensor reading, make sure the sensor is facing the desired motion area within proper distance and angle. |
| Specification Note | Dual Mode Capable: Motion or On-Off Switch |
| Warranty | 2-Years |

Compliance

| | |
|----------------------|-----------------------------------|
| Safety Listing | cULus - Certified; cULus - Listed |
| Location Rating | Wet |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |