

Project Name

Location

Prepared By



SATCO S11476

14PAR38/D2D/LED/950/120V

Notes

(www) 08-11-2024 01:39:53

General

| | |
|-------------------------|---------------|
| Status | Active |
| Watts | 14W |
| Incandescent Equivalent | 90W |
| Volts | 120V |
| Shape | PAR38 |
| Base | Medium |
| ANSI Base | E26 |
| Finish | White |
| CCT (Kelvin) | 5000K |
| Temperature | Natural Light |
| CRI | 90 |
| Lumens | 1250L |
| Beam Spread | 40 |
| Dimmable | Non-Dimmable |
| Hours Rated | 15000 |
| Photocell or Sensor | Has Photocell |
| Product Category | PAR |
| Technology | LED |

Electrical

| | |
|-----------------------|----------------------------|
| Operating Frequency | 60Hz |
| Power Factor | 0.7 |
| Operating Temperature | -20C (-4F) to +40C (+104F) |

Physical

| | |
|---------------|-------|
| MOL | 5.12 |
| MOD | 4.72 |
| Housing Color | White |
| Weight (lb.) | 0.43 |

Additional Information

| | |
|----------------------------|--------------------------------|
| Rated For Enclosed Fixture | No |
| Warranty | 3 Year Limited - 10 hr per day |

Compliance

| | |
|------------------------|-------------|
| Safety Listing | cULus |
| Location Rating | Wet |
| CA T20 / T24 Rationale | T20 Pending |
| RoHS Compliant | Yes |