

Project Name

Location Prepared By



SATCO S11550

5.5W/LED/CFL/827/2P/DUAL

Notes

Status	Active	
Watts	5.5W	
Fluorescent Equivalent	13W	
Volts	120V-277V	
Ballast Type	Type A/B	
Shape	PL	
Base	GX23	
ANSI Base	GX23	
Finish	Frost	
CCT (Kelvin)	2700K	
Temperature	Warm White	
CRI	80+	
Lumens	500L	
Beam Spread	120	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	PL 2-Pin	
Operating Position	Universal	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Power Factor	0.97
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	5.98
MOD	1.26
Housing Color	White
Weight (lb.)	0.11

Additional Information	
Rated For Enclosed Fixture	No
Warranty	5-Years

Compliance	
Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp