

Project Name

Location

Prepared By



SATCO S11550

5.5W/LED/CFL/827/2P/DUAL

Notes

[www] 05-25-2024 03:27:16

General

Status	Active
Watts	5.5W
Fluorescent Equivalent	13W
Volts	120V-277V
Ballast Type	Type A/B
Shape	PL
Base	GX23
ANSI Base	GX23
Finish	Frost
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80
Lumens	500L
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL 2-Pin
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	5.98
MOD	1.26
Housing Color	White
Weight (lb.)	0.13

Additional Information

Rated For Enclosed Fixture	No
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
SDS Sheet	LED_Lamp

