

Project Name

Location

Prepared By



## SATCO S11620

12WLED/DW/GBL/4/930/RND/RD/BN

### Notes

[www] 01-15-2024 02:40:09

### General

Status	Active
Substitute	S11620R1
Wattage	12W
Voltage	120V
Finish	Brushed Nickel
CCT (Kelvin)	3000K
Color Temperature	Warm White
Lumen Output	850L
Indoor or Outdoor Fixture	Indoor

### Specifications

Technology	LED
CRI	90
Beam Angle	40
Rated Hours	50000
Operating Temperature	-20C (-4F) to +45C (+113F)
Dimmable	Yes-Dimmable
Sloped Ceiling	Yes

### Dimensions

Width (in.)	4.88
Height (in.)	2
Weight (lb.)	1.41

### Compliance

Safety Listing	cETLus - Listed
Location Rating	Wet
UL Application	Ceiling
Energy Star	Yes
ES Unique ID	ESID-2337198
DLC Approved	No
Air Tight Rated	Yes
IC Rated	Yes
CA T20 / T24 Rationale	California T24 2016 - 2022 JA8 Listed
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Listed
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

### Additional Information

Additional Information	Integrated j-box for direct wire installation
Specification Note	Aiming Angle: 30dg
Installation Notes	*If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)
Warranty	5 Year Limited - Fixtures

