

Project Name

Location

Prepared By



Notes

(revised) 07-18-2023 00:10:25

General

| | |
|---------------------------|--------------|
| Status | Discontinued |
| Substitute | S11630R1 |
| Wattage | 12W |
| Voltage | 120V |
| Finish | White |
| CCT (Kelvin) | 3000K |
| Color Temperature | Warm White |
| Lumen Output | 840L |
| Indoor or Outdoor Fixture | Indoor |

Specifications

| | |
|-----------------------|----------------------------|
| Technology | LED |
| CRI | 90+ |
| Beam Angle | 40 |
| Rated Hours | 50000 |
| Operating Temperature | -20C (-4F) to +45C (+113F) |
| Dimmable | Yes-Dimmable |
| Sloped Ceiling | No |

Dimensions

| | |
|--------------|------|
| Width (in.) | 4.38 |
| Height (in.) | 3 |
| Weight (lb.) | 1.09 |

Compliance

| | |
|----------------------|-------------------------------|
| Safety Listing | cETLus - Listed |
| Location Rating | Wet |
| UL Application | Ceiling |
| ENERGY STAR | No |
| DLC Approved | No |
| Air Tight Rated | Yes |
| IC Rated | Yes |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | California T24 Listed |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |

Additional Information

| | |
|------------------------|--|
| Additional Information | Integrated j-box for direct wire installation |
| Installation Notes | *If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973) |
| Warranty | 5-Years |