SATCO' NUVO

Project Name

Prepared By



SATCO S11635 12WLED/DW/DNL3/930/SQ/RD/BN

Notes

StatusTransitioningSubstitute\$11635R1Wattage12WVoltage12WFinishBrushed NickelCCT (Kelvin)3000KColor TemperatureWarm WhiteLumen Output840LIndoor or Outdoor FixtureIndoorSpecifications90+Beam Angle40Rated Hours50000Operating Temperature-20C (4F) to +45C (+113F)DinmableYes-DinmableSloped CellingNoDinensions-20C (4F) to +45C (+113F)DismableYes-DinmableSloped CellingNoDinensions-20C (4F) to +45C (+113F)Length (in.)4.38Height (in.)4.38Uidth (in.)4.38Usight (ib.)1.18Compliance	General	
Wattage12WVoltage120VFinishBrushed NickelCCT (kelvin)3000KColor TemperatureWarm WhiteLumen Output840LIndoor or Outdoor FixtureIndoorSpecificationsTechnologyLEDCRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +4SC (+113F)DinmableYes-DinmableSloped CeilingNoDimensionsLength (in.)4.38Weight (ib.)1.18ComplianceSafety ListingCETLus - ListedLocation RatingWetUL ApplicationCeilingNoDLC ApprovedNoDLC ApprovedAir Tight RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*f you purchase The SW Emergency Driver (S8000) or the 10W Emergency Driver (S8000) or yourse the Emergency Driver (S8000) or yourse the Emergency Driver (S8000) or yourse the Course the Emergency Driver Enclosure (80-973)	Status	Transitioning
Voltage120VFinishBrushed NickelCCT (kelvin)3000KColor TemperatureWarm WhiteLumen Output840LIndoor or Outdoor FixtureIndoorSpecificationsTechnologyTechnologyLEDCRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensions1.18Length (in.)4.38Weight (ib.)1.18ComplianceSafety ListingCETLus - ListedLocation RatingUL ApplicationCeilingENRGY STARNoDLC ApprovedNoAir Tight RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia ItatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia ItatusLawful for sale in californiaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in californiaTitle 20 / 24 StatusCalifornia T24 Liste	Substitute	S11635R1
FinishBrushed NickelCCT (Kelvin)3000KColor TemperatureWarm WhiteLumen Output840LIndoor o Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CellingNoDimensionsLength (in.)Length (in.)4.38Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingDIRREY STARNoDLC ApprovedNoAir Tight RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in californiaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in californiaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for direct wire installationKdditional InformationIntegrated j-box for direct wire installationAdditional Informatio	Wattage	12W
CCT (Kelvin)3000KColor TemperatureWarm WhiteLumen Output840LIndoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensionsImage: CellingLength (in.)4.38Weight (ib.)1.18ComplianceImage: CellingSafety ListingCETLus - ListedLocation RatingWetUL ApprovedNoDLC ApprovedNoLi Tight RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia T24 ListedYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*If you purchase The SW Emergency Driver (S8000) or the 10W Emergency Driver (S8000) or the	Voltage	120V
Color TemperatureWarm WhiteLumen Output840LIndoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensionsLength (in.)4.38Weight (ib.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENRGY STARNoDLC ApprovedNoAir Tight RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia InformationYesAdditional InformationIntegrated j-box for direct wire installation*If you purchase The SW Emergency Driver (S8000), you must also purchase the Emergency Driver Enclosure (80-973)	Finish	Brushed Nickel
Lumen Output840LIndoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (.4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensionsLength (in.)Length (in.)4.38Weight (ib.)1.18ComplianceSafety ListingSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSpect ListingCalifornia T24 ListedCalifornia T10YesIC Additional InformationIntegrated j-box for direct wire installation*if you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8001), you must also purchase the Emergency Driver Enclosure (80-973)	CCT (Kelvin)	3000K
Indoor or Outdoor FixtureIndoorSpecificationsIEDTechnologyLEDCRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensionsLength (in.)4.38Width (in.)4.38Height (ib.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingDirming TattaYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*if you purchase The SW Emergency Driver (S8002), you unst also purchase the Emergency Driver (S8002), you unst also purchase the Emergency Driver (S8002), you unst also purchase the Emergency Driver Enclosure (80-973)	Color Temperature	Warm White
SpecificationsTechnologyLEDCRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensionsLength (in.)4.38Width (in.)4.38Height (in.)4.38Weight (Ib.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingDLC ApprovedNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSD SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*if you purchase The SW Emergency Driver (S8002), you wust also purchase the Emergency Driver (S8002), you wust also purchase the Emergency Driver (S8002), you wust also purchase the Emergency Driver Enclosure (80-973)	Lumen Output	840L
TechnologyLEDCRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensionsLength (in.)4.38Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDL ApprovedNoAir Tight RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLeadFCC CompliantYesSD SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*If you purchase The SW Emergency Driver (S8002), you wust also purchase the Emergency Driver (S8002), you wust also purchase the Emergency Driver (S8002), you wust also purchase the Emergency Driver Enclosure (80-973)	Indoor or Outdoor Fixture	Indoor
CRI90+Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensions4.38Width (in.)4.38Height (in.)4.38Height (in.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLeadFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*ff you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S80	Specifications	
Beam Angle40Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensionsLength (in.)4.38Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSD SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*ff you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8000) or t	Technology	LED
Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensions4.38Length (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSD S sheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*If you purchase the SW govor the IOW Emergency Driver (S8000), or the IOW Emergency Driver (S8002), you must also purchase the Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	CRI	90+
Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableSloped CeilingNoDimensions4.38Length (in.)4.38Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*If you purchase The SW Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Beam Angle	40
DimmableYes-DimmableSloped CeilingNoDimensions4.38Length (in.)4.38Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*If you purchase The SW Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Rated Hours	50000
DimmableYes-DimmableSloped CeilingNoDimensions4.38Length (in.)4.38Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*If you purchase The SW Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)		-20C (-4F) to +45C (+113F)
DimensionsLength (in.)4.38Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationNotes"if you purchase The SW Emergency Driver (S8000) or the 10W Emergency Driver (S8000), you must also purchase the Emergency Driver (S8002), you must also purchase the Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Dimmable	Yes-Dimmable
Length (in.)4.38Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationInstallation Notes*If you purchase The SW Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Sloped Ceiling	No
Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationAdditional Information*If you purchase The 5W Emergency Driver (S8000), you must also purchase the Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Dimensions	
Width (in.)4.38Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationAdditional Information*If you purchase The 5W Emergency Driver (S8000), you must also purchase the Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Length (in.)	4.38
Height (in.)3Weight (lb.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationInstallation Notes"If you purchase The 5W Emergency Driver (S8000), you must also purchase the Emergency Driver Enclosure (80-973)		
Weight (Ib.)1.18ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*If you purchase The SW Emergency Driver (S8000) or the 10W Emergency Driver (S8000), you must also purchase the Emergency Driver Enclosure (80-973)		3
Safety ListingcETLus - ListedLocation RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installation*If you purchase The SW Emergency Driver (S8000) or the 10W Emergency Driver (S8000), you must also purchase the Emergency Driver Enclosure (80-973)	Weight (lb.)	1.18
Location RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationAdditional InformationIntegrated j-box for direct wire installationInstallation Notes*If you purchase the Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Compliance	
Location RatingWetUL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationAdditional InformationIntegrated j-box for direct wire installationInstallation Notes*If you purchase the Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Safety Listing	cETLus - Listed
UL ApplicationCeilingENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationNational InformationIntegrated j-box for direct wire installationInstallation NotesS000) or the 10W Emergency Driver (S8000) or ust also purchase the Emergency Driver Enclosure (80-973)		Wet
ENERGY STARNoDLC ApprovedNoAir Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationInstallation Notes"If you purchase The 5W Emergency Driver" (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)		Ceiling
Air Tight RatedYesIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationAdditional InformationIntegrated j-box for direct wire installationInstallation Notes"If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)		
IC Rated Yes California Status Lawful for sale in California Title 20 / 24 Status California T24 Listed California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Lamp Additional Information Integrated j-box for direct wire installation Installation Notes (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	DLC Approved	No
California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_LampAdditional InformationIntegrated j-box for direct wire installationInstallation Notes'If you purchase The 5W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Air Tight Rated	Yes
Title 20 / 24 Status California T24 Listed California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Lamp Additional Information Integrated j-box for direct wire installation Additional Information Integrated j-box for direct wire installation Installation Notes "If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	IC Rated	Yes
California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Lamp Additional Information Integrated j-box for direct wire installation Additional Information Integrated j-box for direct wire installation Installation Notes *If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	California Status	Lawful for sale in California
RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Lamp Additional Information Integrated j-box for direct wire installation Additional Information Integrated j-box for direct wire installation Installation Notes *If you purchase The 5W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Title 20 / 24 Status	California T24 Listed
FCC Compliant Yes SDS Sheet LED_Lamp Additional Information Integrated j-box for direct wire installation Additional Information Integrated j-box for direct wire installation Installation Notes *If you purchase The 5W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	California Prop 65	Lead
SDS Sheet LED_Lamp Additional Information Integrated j-box for direct wire installation Additional Information Integrated j-box for direct wire installation Installation Notes *If you purchase The 5W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	RoHS Compliant	Yes
Additional Information Integrated j-box for direct wire installation Additional Information Integrated j-box for direct wire installation Installation Notes *If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	FCC Compliant	Yes
Additional Information Integrated j-box for direct wire installation *If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	SDS Sheet	LED_Lamp
*If you purchase The 5W Emergency Driver Installation Notes (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Additional Information	
Installation Notes (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)	Additional Information	Integrated j-box for direct wire installation
Warranty 5-Years	Installation Notes	(S8000) or the 10W Emergency Driver (S8002), you must also purchase the
	Warranty	5-Years

