SATCO NUVO

Project Name

ocation Prepared By



Notes

] 10-27-2025 05

Status	Active
Watts	11.5W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Туре В
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Soft White to Daylight
CRI	80+
Lumens	1700L/1750L/1800L/1800L/1750L
Beam Spread	160
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical		
Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required	
Operating Frequency	50/60Hz	
Dimming Type	Reverse Phase	
Dimming Note	120V only	
Power Factor	0.9	
THD	<20%	
Operating Temperature	-20C (-4F) to +45C (+113F)	

Physical	
MOL	47.2
MOD	1
Material	Glass
Housing Color	White
Weight (lb.)	0.47

Additional Information		
Shatter-Proof Type	PET Coated	
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance		
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component	
Location Rating	Damp	
DLC Approved	Yes	
DLC ID	S-9MGCSL	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	Yes	
Flicker Free	Yes	
SDS Sheet	LED_Lamp	