

Project Name

Location

Prepared By



SATCO S11732

15WT8/LED/CCT/EM/BP

Notes

(revised) 07-09-2023 00:10:26

General

Status	Active
Watts	15W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	3500K/4000K/5000K
Temperature	Neutral White to Natural Light
CRI	80+
Lumens	2000L
Beam Spread	140
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Bypass
Operating Frequency	50/60Hz
THD	<25%
Operating Temperature	0C (+32F) to +45C (+113F)

Physical

MOL	47.78
MOD	1.16
Leg Spacing	0.51
Material	Aluminum / Polycarbonate (PC)
Weight (lb.)	1.12

Additional Information

Specification Note	90-minute discharge time; 24 Hour Recharge Time
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cRUus - Recognized Component; cULus - Certified; cULus - Classified
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-ZM2STB
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class A
NSF Approved	Yes
SDS Sheet	LED_Lamp