

Project Name

Location

Prepared By

**SATCO S11741R1**

9.5/T8/LED/48-835/DR

**Notes**

(www) 08-28-2023 23:30:16

**General**

Status	Active
Watts	9.5W
Incandescent Equivalent	75W
Fluorescent Equivalent	32W/30W/28W/25W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	1740L
Beam Spread	210
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

**Electrical**

Ballasting Requirements	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Operating Frequency	50/60Hz
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

**Physical**

MOL	47.78
MOD	1.1
Material	Glass / Steel
Housing Color	White
Weight (lb.)	0.38

**Additional Information**

Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

**Compliance**

Safety Listing	cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-0K7BB4
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp