

Project Name

Location

Prepared By



Notes

[www] 05-15-2024 04:42:54

General

Status	Active
Watts	9.5W
Incandescent Equivalent	75W
Fluorescent Equivalent	32W/30W/28W/25W
Volts	120V-277V
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	82
Lumens	1740L
Beam Spread	210
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Operating Frequency	50/60Hz
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	48
MOD	1
Material	Glass
Housing Color	White
Weight (lb.)	0.42

Additional Information

Installation Notes	Not for use in vapor tight fixtures.
Specification Note	Surge Protection
Warranty	5 Year Limited - T8 LED Bulbs

Compliance

Safety Listing	cULus - Listed
Location Rating	Damp
Energy Star	No
DLC Approved	Yes

DLC ID	PLRBCA9H3Z8T
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc.
All Rights Reserved

For More Information Visit:
<https://www.satco.com/>

