

SATCO S11742 9.5/T8/LED/48-840/DR

Notes

w1 10-27-2025 05:20:

Status	Active	
Substitute	S11742R1	
Watts	9.5W	
Incandescent Equivalent	75W	
Fluorescent Equivalent	32W/30W/28W/25W	
Volts	Ballast Dependent	
Ballast Type	Type A	
Shape	T8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	48	
Finish	Gloss	
CCT (Kelvin)	4000K	
Temperature	Cool White	
CRI	80+	
Lumens	1740L	
Beam Spread	210	
Dimmable	Yes-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart	
50/60Hz	
Only in Type A mode; Check Ballast MFG for Dimmer Compatibility	
0.9	
20%	
-20C (-4F) to +45C (+113F)	

Physical		
MOL	48	
MOD	1	
Material	Glass	
Housing Color	White	
Weight (lb.)	0.41	

Additional Information		
Installation Notes	Not for use in vapor tight fixtures.	
Specification Note	Surge Protection	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Certified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLRBCA9H3Z8T
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp

