		SATCO NUVO
Project Name		
Location	Prepared By	
C C C C		
SATCO S	11750	

Notes

w] 10-27-2025 05:20

Status	Active
Watts	14W
Incandescent Equivalent	75W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	48
Finish	White
CCT (Kelvin)	4000K/5000K/6500K
Temperature	Cool White to Daylight
CRI	80+
Lumens	1950L/2000L/1900L
Beam Spread	180
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical		
Ballasting Requirements	Ballast Bypass	
Operating Frequency	50/60Hz	
Power Factor	0.9	
THD	<25%	
Operating Temperature	-20C (-4F) to +45C (+113F)	

Physical	
MOL	46
MOD	1
Material	Glass / Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.56

Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance		
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component	
Location Rating	Damp	
DLC Approved	No	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	Yes	
SDS Sheet	LED_Lamp	