		SATCO 'I NUVO'
Project Name		
Location	Prepared By	
4 Fee		
SATCO S 38T8/LED/96-CCT/BP/FA8	11752	

Notes

General	
Status	Active
Watts	38W
Incandescent Equivalent	150W
Fluorescent Equivalent	59W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	96
Finish	White
CCT (Kelvin)	4000K/5000K/6500K
Temperature	Cool White to Daylight
CRI	80+
Lumens	5400L/5500L/5300L
Beam Spread	180
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	<25%

Electrical		
Ballasting Requirements	Ballast Bypass	
Operating Frequency	50/60Hz	
Power Factor	0.9	
THD	<25%	
Operating Temperature	-20C (-4F) to +45C (+113F)	
Plantage		

Physical	
MOL	93.88
MOD	1
Material	Glass / Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	1.32

Additional Information		
Includes	Each master case contains a 10 pack of item 80-984 (LED T8 Support Clip.)	
Shatter-Proof Type	PET Coated	
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

cULus - Certified; cULus - Classified; cRUus - Recognized Component	
Damp	
Yes	
S-QP7NDI	
Lawful for sale in California	
Lawful for sale	
Yes	
Yes	
Yes	
LED_Lamp	