		<b>SATCO</b> INUVO
Project Name		
Location	Prepared By	
	<u> </u>	
4 Fee		
245	-	
SATCO S 38T8/LED/96-CCT/BP/FA8	11752	

Notes

General	
Status	Active
Watts	38W
Incandescent Equivalent	150W
Fluorescent Equivalent	59W
Volts	120V-277V
Ballast Type	Туре В
Shape	Т8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	96
Finish	White
CCT (Kelvin)	4000K/5000K/6500K
Temperature	Cool White to Daylight
CRI	80+
Lumens	5400L/5500L/5300L
Beam Spread	180
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	<25%
Operating Temperature	-20C (-4F) to +45C (+113F)

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	<25%
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	02.00

Physical		
MOL	93.88	_
MOD	1	
Material	Glass / Plastic	
Lens Finish	Frost	
Lens Material	Glass	
Housing Color	White	
Weight (lb.)	1.32	

Additional Information		
Includes	Each master case contains a 10 pack of item 80-984 (LED T8 Support Clip.)	
Shatter-Proof Type	PET Coated	
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance		
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component	
Location Rating	Damp	
DLC Approved	Yes	
DLC ID	S-QP7NDI	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	Yes	
SDS Sheet	LED_Lamp	