		SATCO NUVO
Project Name		
Location	Prepared By	
Na cincimi		
SATCO S 40T8/LED/96-CCT/BP/R2PC		

Notes

Status	Active
Watts	24W/32W/40W
ncandescent Equivalent	100W
Fluorescent Equivalent	59W/86W/96W
Volts	120V-277V
Ballast Type	Туре В
Shape	Т8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	96
Finish	White
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Soft White to Daylight
CRI	80+
Lumens	3500L/4400L/5500L
Beam Spread	210
Hours Rated	50000
Product Category	Linear
Technology	LED

Operating Frequency	50/60Hz	
Power Factor	0.9	
THD	<25%	
Operating Temperature	-20C (-4F) to +45C (+113F)	
Physical		
MOL	93.75	
MOD	1	
Material	Glass	
Housing Color	White	
Weight (lb.)	0.98	

Ballast Bypass

Additional Information		
Includes	(1) Set R17d Endcaps; (1) C-Clip	
Shatter-Proof Type	PET Coated	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance		
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component	
Location Rating	Damp	
DLC Approved	Yes	
DLC ID	S-J3JX31	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	Yes	
SDS Sheet	LED_Lamp	

Ballasting Requirements