

Project Name

Location

Prepared By



# SATCO S11757

40T8/LED/96-CCT/BP/R2PC/1PK

## Notes

(www) 08-28-2023 23:30:16

## General

Status	Active
Watts	24W/32W/40W
Incandescent Equivalent	100W
Fluorescent Equivalent	59W/86W/96W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	96
Finish	White
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Soft White to Daylight
CRI	80+
Lumens	3500L/4400L/5500L
Beam Spread	210
Hours Rated	50000
Product Category	Linear
Technology	LED

## Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	<25%
Operating Temperature	-20C (-4F) to +45C (+113F)

## Physical

MOL	93.75
MOD	1
Material	Glass
Housing Color	White
Weight (lb.)	0.98

## Additional Information

Includes	(1) Set R17d Endcaps; (1) C-Clip
Shatter-Proof Type	PET Coated
Rated For Enclosed Fixture	Yes
Warranty	5-Years

## Compliance

Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-J3JX31
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp