

SATCO S11764

9T8/LED/24-5CCT/BP/SE-DE

Notes

General	
Status	Active
Watts	9W
Incandescent Equivalent	40W
Fluorescent Equivalent	17W
Volts	120V-277V
Ballast Type	Type B
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	White
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Warm White to Daylight
CRI	80
Lumens	1150L/1150L/1250L/1250L/1250L
Beam Spread	210
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
	Della et Desa es
Ballasting Requirements	Ballast Bypass 50/60Hz
Operating Frequency Power Factor	0.9
THD	<25%
Operating Temperature	-20C (-4F) to +45C (+113F)
	-200 (-41) to +430 (+1131)
Physical	
MOL	23.17
MOD	1
Material	Glass / Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.25
Additional Information	
	N OOT O I I I I I I I I I I I I I I I I I
Additional Info	Non CCT Selectable options are S39900-S39903
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
	5 Year Limited - T8 LED Bulbs -
Warranty	Ballast Bypass
Compliance	
	allius Olas W. J. IV
Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	S-N3X0KC
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California

Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



