		SATCO 'I NUVO'
Project Name		
Location	Prepared By	
MARCO 3170		
MARINE AND STREET		
SATCO S11764 9T8/LED/24-5CCT/BP/SE-DE		

Notes

Status	Active
Watts	9W
ncandescent Equivalent	40W
Fluorescent Equivalent	17W
Volts	120V-277V
Ballast Type	Туре В
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
inish	White
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Warm White to Daylight
CRI	80+
Lumens	1150L/1150L/1250L/1250L/1250L
Beam Spread	210
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical		
Ballasting Requirements	Ballast Bypass	
Operating Frequency	50/60Hz	
Power Factor	0.9	
THD	<25%	
Operating Temperature	-20C (-4F) to +45C (+113F)	

Physical	
MOL	23.17
MOD	1
Material	Glass / Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.25

Additional Information	
Additional Info	Non CCT Selectable options are S39900- S39903
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-N3X0KC
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp