SATCO' NUVO

Project Name

Location Prepared By



SATCO S11801

9WLED/RDL/5-6/ADJ-CCT/120V

Notes

StatusDiscontinuedSubstituteS11801R1Recessed Can Size5-6 in.Wattage9WVoltage120VFinishWhiteCCT (Kelvin)2700K/3000K/3500K/4000K/5000KColor TemperatureWarm to Cool WhiteLumen Output800LIndoor or Outdoor FixtureB00LBeam Angle90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DirmmableYes-DirmmableVidth (in.)7.4Height (in.)3.25Safet JustingCULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia 24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantSize Adapter included (S9001)WarrantySizers	General	
Recessed Can Size5-6 in.Wattage9WVoltage120VFinishWhiteCCT (kelvin)2700K/3000K/3500K/4000K/5000KColor TemperatureWarm to Cool WhiteLumen Output800LIndoor or Outdoor FixtureIndoorSpecificationsEDTechnologyLEDCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensions7.4Height (in.)7.4Height (ib.)0.78ComplianceSolus - Classified; cULus - CertifiedLocation RatingWetDL ApprovedNoCalifornia StatusCalifornia T24 ListedCalifornia StatusCalifornia T24 ListedCalifornia T24 ListedCalifornia T24 ListedCalifornia InformationYesSD SheetLED_FixtureAdditional InformationFixtureIncludesE26 Adapter included (S9001)	Status	Discontinued
Wattage9WVoltage120VFinishWhiteCCT (Kelvin)2700K/3000K/3500K/4000K/5000KColor TemperatureWarm to Cool WhiteLumen Output800LIndoor or Outdoor FixtureIndoorSpecificationsEEDCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensions-20C (-4F) to +45C (+113F)Width (in.)7.4Height (ib.)0.78Compliance-20CSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadReHS CompliantYesFCC CompliantYesSp SheetLED_FixtureAdditional InformationYesIncludesE26 Adapter included (S9001)	Substitute	S11801R1
NotageInterventionVoltage120VFinishWhiteCCT (Kelvin)2700K/3000K/3500K/4000K/5000KColor TemperatureWarm to Cool WhiteLumen Output800LIndoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsYesWidth (in.)7.4Height (in.)3.25Wight (b.)0.78ComplianceSolus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSD SheetLED_FixtureAdditional InformationF26 Adapter included (S9001)	Recessed Can Size	5-6 in.
FinishWhiteCCT (Kelvin)2700K/3000K/3500K/4000K/5000KColor TemperatureWarm to Cool WhiteLumen Output800LIndoor or Outdoor FixtureIndoorSpecificationsTechnologyCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsWidth (in.)7.4Height (in.)3.25Weight (b.)0.78ComplianceSafety ListingLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationYesIncludesE26 Adapter included (S9001)	Wattage	9W
CCT (Kelvin)2700K/3000K/3500K/4000K/5000KColor TemperatureWarm to Cool WhiteLumen Output800LIndoor or Outdoor FixtureIndoorSpecificationsTechnologyCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Voltage	120V
Color TemperatureWarm to Cool WhiteLumen Output800LIndoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsYes-DimmableWidth (in.)7.4Height (in.)3.25Width (lb.)0.78ComplianceYesSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationYesIncludesE26 Adapter included (S9001)	Finish	White
Lumen Output800LIndoor or Outdoor FixtureIndoorSpecificationsETechnologyLEDCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsJumensionsWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDL C ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
IndoorIndoorSpecificationsIndoorTechnologyLEDCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsWidth (in.)7.4Height (in.)3.25Wight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDL C ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationYesIncludesE26 Adapter included (S9001)	Color Temperature	Warm to Cool White
SpecificationsTechnologyLEDCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsVestoreWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Lumen Output	800L
TechnologyLEDCRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Indoor or Outdoor Fixture	Indoor
CRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Specifications	
CRI90+Beam Angle90Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Technology	LED
Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsYes-DimmableWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceUlus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	CRI	90+
Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsYes-DimmableWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceUllus - Classified; cULus - CertifiedSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRCC CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Beam Angle	90
DimmableYes-DimmableDimensionsWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Rated Hours	50000
DimensionsWidth (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Operating Temperature	-20C (-4F) to +45C (+113F)
Width (in.)7.4Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Dimmable	Yes-Dimmable
Height (in.)3.25Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Dimensions	
Weight (lb.)0.78ComplianceSafety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationIncludesE26 Adapter included (S9001)	Width (in.)	7.4
Compliance Safety Listing cULus - Classified; cULus - Certified Location Rating Wet DLC Approved No IC Rated Yes California Status Lawful for sale in California Title 20 / 24 Status California T24 Listed California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information E26 Adapter included (S9001)	Height (in.)	3.25
Safety ListingcULus - Classified; cULus - CertifiedLocation RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationIncludesE26 Adapter included (S9001)	Weight (lb.)	0.78
Location RatingWetDLC ApprovedNoIC RatedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	Compliance	
DLC Approved No IC Rated Yes California Status Lawful for sale in California Title 20 / 24 Status California T24 Listed California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information E26 Adapter included (S9001)	Safety Listing	cULus - Classified; cULus - Certified
IC Rated Yes California Status Lawful for sale in California Title 20 / 24 Status California T24 Listed California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information E26 Adapter included (S9001)	Location Rating	Wet
California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationE26 Adapter included (S9001)	DLC Approved	No
Title 20 / 24 Status California T24 Listed California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information E26 Adapter included (S9001)	IC Rated	Yes
California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information E26 Adapter included (S9001)	California Status	Lawful for sale in California
RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information E26 Adapter included (S9001)	Title 20 / 24 Status	California T24 Listed
FCC Compliant Yes SDS Sheet LED_Fixture Additional Information E26 Adapter included (S9001)	California Prop 65	Lead
SDS Sheet LED_Fixture Additional Information E26 Adapter included (S9001)	RoHS Compliant	Yes
Additional Information Includes E26 Adapter included (S9001)	FCC Compliant	Yes
Includes E26 Adapter included (S9001)	SDS Sheet	LED_Fixture
	Additional Information	
Warranty 5-Years	Includes	E26 Adapter included (S9001)
	Warranty	5-Years