

Project Name

Location

Prepared By



# SATCO S11830

12WLED/DW/EL/6/CCT-SEL/SQ/RD

## Notes

(revised) 07-09-2023 00:10:01

## General

Status	Active
Substitute	S11830R1
Recessed Can Size	6 in.
Wattage	12W
Voltage	120V
Finish	White
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Color Temperature	Warm to Cool White
Lumen Output	750L
Indoor or Outdoor Fixture	Indoor

## Specifications

Technology	LED
CRI	90+
Beam Angle	108
Rated Hours	50000
Operating Temperature	-20C (-4F) to +45C (+113F)
Dimmable	Yes-Dimmable
Sloped Ceiling	No

## Dimensions

Length (in.)	6.69
Width (in.)	6.69
Height (in.)	0.9
Weight (lb.)	1.16

## Compliance

Safety Listing	cETLus - Listed
Location Rating	Wet
ENERGY STAR	No
DLC Approved	No
Air Tight Rated	Yes
IC Rated	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Listed
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class B
SDS Sheet	LED_Lamp

## Additional Information

Additional Information	Candlepower: 290
Specification Note	Lumens (L) vary with color temperature (K): 2700K 700L / 3000K 720L / 3500K 760L / 4000K 760L / 5000K 750L
Installation Notes	*If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)
Warranty	5-Years