

Notes

2W/LED/T5/840/BP

v] 10-27-2025 05:

Status	Active	
Watts	2W	
Incandescent Equivalent	15W	
Fluorescent Equivalent	4W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	T5	
Base	Miniature Bi Pin	
ANSI Base	G5	
Nominal Length	6	
Finish	Frost	
CCT (Kelvin)	4000K	
Temperature	Cool White	
CRI	80+	
Lumens	150L	
Beam Spread	240	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	No ballast or external driver required
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-25C (-13F) to +45C (+113F)

Physical	
MOL	5.91
MOD	0.83
Material	Glass
Lens Finish	Frost
Weight (lb.)	0.08

Additional Information		
Additional Info	Replaces F4T5/CW lamps; All glass tube	
Shatter-Proof Type	PET Coated	
Installation Notes	Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp