

Project Name

Location

Prepared By



SATCO S11905

4W/LED/T5/840/BP

Notes

(www) 18-17-2023 05:20:07

General

| | |
|-------------------------|------------------|
| Status | Active |
| Watts | 4W |
| Incandescent Equivalent | 25W |
| Fluorescent Equivalent | 8W |
| Volts | 120V-277V |
| Ballast Type | Type B |
| Shape | T5 |
| Base | Miniature Bi Pin |
| ANSI Base | G5 |
| Nominal Length | 12 |
| Finish | Frost |
| CCT (Kelvin) | 4000K |
| Temperature | Cool White |
| CRI | 80+ |
| Lumens | 400L |
| Beam Spread | 240 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Product Category | Linear |
| Technology | LED |

Electrical

| | |
|-------------------------|--|
| Ballasting Requirements | No ballast or external driver required |
| Operating Frequency | 50/60Hz |
| Power Factor | 0.9 |
| THD | 20% |
| Operating Temperature | -25C (-13F) to +45C (+113F) |

Physical

| | |
|--------------|-------|
| MOL | 11.91 |
| MOD | 0.83 |
| Material | Glass |
| Lens Finish | Frost |
| Weight (lb.) | 0.13 |

Additional Information

| | |
|----------------------------|---|
| Additional Info | Replaces F8T5/CW lamps |
| Shatter-Proof Type | PET Coated |
| Installation Notes | Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring |
| Rated For Enclosed Fixture | Yes |
| Warranty | 5-Years |

Compliance

| | |
|----------------------|--|
| Safety Listing | cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component |
| Location Rating | Damp |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| Colorado Status | Lawful for sale |
| Hawaii Status | Lawful for sale |
| Nevada Status | Lawful for sale |
| Vermont Status | Lawful for sale |
| Washington Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |