

Notes

rw1 10-27-2025 05:20:50

General	
Status	Active
Watts	18.5W
Incandescent Equivalent	90W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Туре В
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	24001
Lumens Beam Spread	2400L 180
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Operating Frequency	60Hz
Power Factor	0.92
THD Operation Temporature	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	47.78
MOD	1
Material	Glass
Lens Finish Lens Material	Frost Glass
Housing Color	White
Weight (lb.)	0.49
Additional Information	
	Installation protection - will not light if ballast
Additional Info	is not bypassed.
Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures. Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring
Rated For Enclosed Fixture	Yes
Warranty	5-Years
Compliance	
Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLD6BIXNDD9U
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status RoHS Compliant	Lawful for sale Yes
FCC Compliant	
	Yes ETI Sanitation listed (conforms to NSE)
NSF Approved Flicker Free	ETL Sanitation listed (conforms to NSF) Yes
CDC Chast	TES Lemm

LED_Lamp

SDS Sheet