SATCO NUVO

Project Name

Location

Prepared By



SATCO S11915

18.5T8/LED/48-835/LF/BP

Notes

General	
Status	Active
Watts	18.5W
Incandescent Equivalent	90W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Туре В
Shape	
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48 Freet
Finish	Frost
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	2400L
Beam Spread	180
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver require
Operating Frequency	60Hz
Power Factor	0.92
ТНР	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
	200(11)101100(11101)
Physical	
MOL	47.78
MOD	1
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.49
Additional Information	
Additional Info	Installation protection - will not light if ballas is not bypassed.
Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures. Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring
Rated For Enclosed Fixture	Yes
Warranty	5-Years
Compliance	
Compliance Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation
	Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLD6BIXNDD9U
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)
Flicker Free	Yes

