		<b>SATCO</b> NUVO
Project Name		
Location	Prepared By	
1000年を主義		
<b>SATCO S</b> 18.5T8/LED/48-840/LF/BP	11916	

Notes

Status	Active
Watts	18.5W
Incandescent Equivalent	90W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	2500L
Beam Spread	180
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Power Factor	0.92
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	47.78
MOD	1
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.47

Additional Information		
Additional Info	Installation protection - will not light if ballast is not bypassed.	
Shatter-Proof Type	PET Coated	
Installation Notes	Not for use in vapor tight fixtures. Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance		
Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation Recognized Component	
Location Rating	Damp	
DLC Approved	Yes	
DLC ID	PLA9OZCCPT5Z	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
Colorado Status	Lawful for sale	
Hawaii Status	Lawful for sale	
Nevada Status	Lawful for sale	
Vermont Status	Lawful for sale	
Washington Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	ETL Sanitation listed (conforms to NSF)	
Flicker Free	Yes	
SDS Sheet	LED Lamp	