

Notes

**SATCO S11920** 

13.5T8/LED/48-830/DIM-BP

Status	Discontinued
Substitute	S11664
Watts	13.5W
Incandescent Equivalent	70W
Fluorescent Equivalent	25W
Volts	120V
Ballast Type	Туре В
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	3000K
Temperature	Warm White
CRI	80+
Lumens	1700L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120V line voltage No ballast or external driver required
Operating Frequency	60Hz
Dimming Type	Reverse Phase or Phase Selectable
Dawer Faster	0.0

Ballasting Requirements	Ballast Bypass; Direct wire 120V line voltage No ballast or external driver required
Operating Frequency	60Hz
Dimming Type	Reverse Phase or Phase Selectable
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	48
MOD	1
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.45

Additional Information	
Tube Guard Use	Yes
Installation Notes	Not for use in vapor tight fixtures. Install only in non-shunted lampholders
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
cULus - Classified; cULus - Certified	
Damp	
Yes	
PLV12B1YBIYP	
Lawful for sale in California	
Lawful for sale	
Yes	
Yes	
Yes	
LED_Lamp	