

Project Name

ocation Prepared By



Notes

w] 09-09-2025 21:53

Status	Discontinued	
Substitute	S11664	
Watts	13.5W	
Incandescent Equivalent	70W	
Fluorescent Equivalent	25W	
Volts	120V	
Ballast Type	Туре В	
Shape	Т8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	48	
Finish	Frost	
CCT (Kelvin)	4000K	
Temperature	Cool White	
CRI	80+	
Lumens	1800L	
Beam Spread	220	
Dimmable	Yes-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120V line voltage; No ballast or external driver required
Dimming Type	Reverse Phase or Phase Selectable
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	48
MOD	1
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.45

Additional Information	
Tube Guard Use	Yes
Installation Notes	Not for use in vapor tight fixtures. Install only in non-shunted lampholders
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLCHL8NP6U2O
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp